

DISPOSITIVO PARA REDUCIR RIESGOS DE FUEGO O EXPLOSION

LOS CARRETES PARA DESCARGA DE ESTATICA SON USADOS PARA EL ATERRIZAMIENTO DE EQUIPOS INSTALADOS EN AMBIENTES DE ALTO RIESGO TALES COMO AUTOTANQUES O TRANSPORTES CON MATERIALES INFLAMABLES

CUANDO EL RIEL ESTA SUJETO AL SUELO O DEBIDAMENTE ATERRIZADO EL CARRETE DISIPA LA ACUMULACION DE ELECTRICIDAD ESTATICA Y REDUCE LA POSIBILIDAD DE FORMACION DE CHISPAS Y EXPLOSIONES.



Features & Benefits

- Automatic spring rewind
- Rugged steel construction
- Compact enclosed design
- Positive ratchet lock
- Lock on/Lock off switch
- Steel cable installed
- Stores cable quickly and easily
- 100 amp universal jaw-type grounding clamp
- Durable baked-on powder coat finish
- Eliminates tangled cable
- Reduces the risk of fire and explosion

REEL SPECIFICATIONS AND DIMENSIONS

Part Number	G 3050 N
Series	G 3050
Weight (Lbs)	12
Reel Grade	HEAVY DUTY
Cable Diameter	1/8" O.D.
Cable Cover	Nylon
Cable Length (ft)	50
Clamp Rating (AMP)	100
Max Temperature (°F)	150

A	8.81"
B	8.62"
C	7.88"
D	1.5"
E	3.35"

